

Groves Incorporated

Manufacturers of Ready Rack and Groves Glass & Stone Storage Systems
818 Trakk Lane, Woodstock, IL 60098 - USA Phone: +1 800-991-2120 Fax: 815-338-8640
www.groves.com e-mail: sales@groves.com

General Use and Safety Guidelines

UNIVERSAL STORAGE SYSTEM (USS-5)

1. Do not exceed recommended maximum weight capacity for each opening (set of two posts):
Universal Storage System = 500 lbs. max capacity per opening (material resting on two posts).
(***Note: The max weight capacities listed are static, and do not take into consideration impact or dynamic forces.)
2. Always be sure posts extend all the way to the floor (through both the top and bottom openings inside the bottom rail), and that each post has its opposing post inserted in the same corresponding slot on the other bottom rail.
3. Be sure there is no debris inside the bottom rails that would prevent the posts from coming in direct contact with the floor.
4. Ensure proper lean to the material being stored. Also, be sure material is centered between the two bottom rails.
5. For added stability, if joining multiple sections of bottom rails, stagger the 2x4 wood sections along half of each adjoining rail.

IMPORTANT NOTE: If you have questions concerning any of the above guidelines, or any product not specifically mentioned, please contact Groves Incorporated immediately for further information. 800-991-2120



Warning: This product can expose you to chemicals including Di (2-ethylhexyl) Phthalate (DEHP), which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.